

TSC

The Smarter Choice.



TTP-244 PRO Desktop Thermal Transfer Bar Code Printer **AFFORDABLE PRICE, FAST PERFORMANCE, WONT BREAK YOUR BAR CODE BUDGET**



KEY FEATURES

- 200 MHz 32-bit RISC processor with 8 MB SDRAM, 4 MB Flash memory
- Internally scalable true type fonts
- TSPL-EZ™ firmware emulates Eltron® and Zebra® languages out of the box
- Dual-motor gear driven design
- 300 meter (984) ribbon supply on a 25.4 mm (1) core (coated side out)
- 110 mm (4.3) OD internal media supply, optional external roll mount supports 214 mm (8.4) OD label rolls on 76.2 mm (3) core
- 5 inches per second print speed
- USB 2.0 & RS-232 interfaces standard
- Free bundled labeling software and Windows drivers

APPLICATIONS

- Shipping & Receiving
- Compliance Labeling
- Asset Tracking
- Inventory Control
- Document Management
- Shelf Labeling & Product Marking
- Specimen Labeling & Patient Tracking

TTP-244 PRO Desktop Thermal Transfer Bar Code Printer

PRINTER MODEL	TTP-244 PRO
Resolution	8 dots/mm (203 DPI)
Printing method	Thermal Transfer & Direct Thermal
Max. print speed	127 mm (5)/second
Max. print width	108 mm (4.25)
Max. print length	2,286 mm (90)
Enclosure	ABS plastic
Physical dimension	232 mm (W) x 156 mm (H) x 288 mm (D) 9.13 (W) x 6.14 (H) x 11.34 (D)
Weight	2.5 kg (5.51 lbs)
Label roll capacity	110 mm (4.33) OD
Ribbon	300 m long, max. OD 67 mm, 1 core (ink coated outside)
Ribbon width	40 mm ~ 110 mm (1.6 ~ 4.3)
Processor	32-bit RISC CPU
Memory	4 MB Flash memory 8 MB SDRAM SD card reader for Flash memory expansion, up to 4 GB (user option)
Interface	USB 2.0 RS-232 Centronics (factory option) Bluetooth (user option)
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz Output: DC 24V, 2.5A, 60W
Operation switch, button, LED	1 power switch, 1 feed button & 3 LED (Power, Error, On-line)
Sensors	Gap transmissive sensor Black mark reflective sensor Ribbon end sensor
Internal fonts	8 alpha-numeric bitmap fonts Monotype Image [®] true type font engine with one CG Triumvirate Bold Condensed scalable font
Bar code	1D bar code Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11 2D bar code PDF-417, Maxicode, DataMatrix, QR Code, Aztec
Font and barcode rotation	0, 90, 180, 270 degree
Printer language	TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II)
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)
Media width	25.4 ~ 112 mm (1.0 ~ 4.4)
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)
Media core diameter	25.4 ~ 76.2 mm (1 ~ 3)
Label length	10 ~ 2,286 mm (0.39 ~ 90)
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Safety regulation	FCC Class A, CE Class A, C-Tick Class A, TTFV/Safety, CCC
Environmental concern	Comply with RoHS, WEEE
Accessories	Windows labeling software CD disk Quick start guide Power cord External universal switching power supply Label spindle, fixing tab x 2 Ribbon spindle x 2 Ribbon paper core
Warranty :	1 year warranty on Printer and *6 months conditional warranty on print head
Factory options	Centronics parallel & RS-232 serial interfaces
Dealer options	N/A
User options	Bluetooth module (serial interface) External roll mount, media OD. 214 mm (8.4) on a 1 or 3 core SD Flash memory card reader 3 core label spindle KP-200 Plus keyboard display unit KU-007 Plus programmable smart keyboard



TSC
The Smarter Choice.