

Thermal Receipt Printers

HOP - E801

Features

- LAN / USB
- Auto Cutter



Item	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing width	72mm
	Resolution	576 Dots/Line or 512 Dots/Line (8dots/mm, 203dpi)
	Print speed	260mm/Second
	Interface	USB, Internet, Internet+USB+COM, Internet+USB+WIFI, USB+COM, USB+Bluetooth, USB+WIFI
	Line Spacing	3.75mm (Can adjust line spacing by command)
	Line No.	FontA-48Lines/FontB-64Lines
	Character Size	ANK character, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)
	Bar code Character	Extended character set
	Bar code	1D bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8) CODE39/ITF/CODABAR/CODE93/CODE128 2D barcode: QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Cutter	Cutter Function	Full cut/Half cut
Paper	Type	Thermal
	Width	79.5±0.5mm
	Diameter	≤80mm
	Feed method	Easy feed(Clameshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input: AC 100V-240V,50-60Hz Output: DC 24V/2.5A
	Cash Drawer	OutputDC 24V/1A
Buffer	Input Buffer	2048K bytes
	NV Flash	256K bytes
Physical characteristics	Weight	1.15KG
	Dimension	195*140*148(MM)
Environment	Working	Temp: 5 ~ 45°C, Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50°C, Humidity: 10 ~ 90% (No dew)
Warranty	1 year warranty on Printer and *6 months conditional warranty on print head.	
Software	Driver	Android, IOS, Linux, Windows